

DB-1701

- (14%-Cyanopropyl-phenyl) methylpolysiloxane

| ID(mm) | Length | Film | Iso/Prog | Cat. No. | |
|-------------|-------------|--------|----------|-----------------|------------------|
| 0.10 | 20m | 0.10µm | 280/300 | 127-0722 | |
| | 20m | 0.40µm | 280/300 | 127-0723 | |
| 0.18 | 10m | 0.40µm | 280/300 | 121-0713 | |
| | 20m | 0.40µm | 280/300 | 121-0723 | |
| 0.20 | 25m | 0.20µm | 280/300 | 128-0722 | |
| | 0.25 | 15m | 0.15µm | 280/300 | 122-0711 |
| 0.25 | 15m | 0.25µm | 280/300 | 122-0712 | |
| | 15m | 1.00µm | 280/300 | 122-0713 | |
| | 30m | 0.15µm | 280/300 | 122-0731 | |
| | 30m | 0.25µm | 280/300 | 122-0732 | |
| | 30m | 1.00µm | 280/300 | 122-0733 | |
| | 60m | 0.15µm | 280/300 | 122-0761 | |
| | 60m | 0.25µm | 280/300 | 122-0762 | |
| | 60m | 0.50µm | 280/300 | 122-0766 | |
| | 60m | 1.00µm | 280/300 | 122-0763 | |
| | 0.32 | 15m | 0.15µm | 280/300 | 123-0711 |
| | | 15m | 0.25µm | 280/300 | 123-0712 |
| | | 15m | 1.00µm | 280/300 | 123-0713 |
| | | 30m | 0.10µm | 280/300 | 123-0739 |
| | | 30m | 0.15µm | 280/300 | 123-0731 |
| 30m | | 0.25µm | 280/300 | 123-0732 | |
| 30m | | 1.00µm | 280/300 | 123-0733 | |
| 50m | | 1.00µm | 280/300 | 123-0753 | |
| 60m | | 0.15µm | 280/300 | 123-0761 | |
| 60m | | 0.25µm | 280/300 | 123-0762 | |
| 60m | | 1.00µm | 280/300 | 123-0763 | |
| 0.45 | | 30m | 0.42µm | 260/280 | 124-0737* |
| | | 30m | 0.85µm | 260/280 | 124-0732* |
| 0.53 | | 15m | 0.50µm | 260/280 | 125-0717 |
| | 15m | 1.00µm | 260/280 | 125-0712 | |
| | 30m | 0.10µm | 260/280 | 125-0739 | |
| | 30m | 0.25µm | 260/280 | 125-0731 | |
| | 30m | 0.50µm | 260/280 | 125-0737 | |
| | 30m | 1.00µm | 260/280 | 125-0732 | |
| | 60m | 1.50µm | 260/280 | 125-0763 | |

*No special ferrules required for High Speed Megabore 0.45mm I.D.

DB-WAX

- Polyethylene glycol (PEG)
- Close equivalent to USP Phase G16
- High polarity
- 20° C lower temperature limit

| ID(mm) | Length | Film | Iso/Prog | Cat. No. |
|-------------|--------|--------|----------|-----------------|
| 0.05 | 10m | 0.05µm | 250/260 | 126-7012 |
| | 10m | 0.10µm | 250/260 | 126-7013 |
| 0.10 | 10m | 0.10µm | 250/260 | 127-7012 |
| | 10m | 0.20µm | 250/260 | 127-7013 |
| | 20m | 0.10µm | 250/260 | 127-7022 |
| | 20m | 0.20µm | 250/260 | 127-7023 |
| 0.18 | 10m | 0.18µm | 250/260 | 121-7012 |
| | 10m | 0.30µm | 250/260 | 121-7013 |
| | 20m | 0.18µm | 250/260 | 121-7022 |
| | 20m | 0.30µm | 250/260 | 121-7023 |
| | 40m | 0.30µm | 250/260 | 121-7043 |

DB-WAX Continued

| ID(mm) | Length | Film | Iso/Prog | Cat. No. | |
|-------------|-------------|---------|-----------------|-----------------|------------------|
| 0.20 | 25m | 0.20µm | 250/260 | 128-7022 | |
| | 25m | 0.20µm | 250/260 | 128-7032 | |
| | 50m | 0.20µm | 250/260 | 128-7052 | |
| | 50m | 0.40µm | 240/250 | 128-7053 | |
| | 60m | 0.20µm | 250/260 | 128-7062 | |
| 0.25 | 15m | 0.15µm | 250/260 | 122-7011 | |
| | 15m | 0.25µm | 250/260 | 122-7012 | |
| | 15m | 0.50µm | 240/250 | 122-7013 | |
| | 30m | 0.15µm | 250/260 | 122-7031 | |
| | 30m | 0.25µm | 250/260 | 122-7032 | |
| | 30m | 0.50µm | 240/250 | 122-7033 | |
| | 60m | 0.15µm | 250/260 | 122-7061 | |
| | 60m | 0.25µm | 250/260 | 122-7062 | |
| | 60m | 0.50µm | 240/250 | 122-7063 | |
| | 0.32 | 15m | 0.15µm | 250/260 | 123-7011 |
| 15m | | 0.25µm | 250/260 | 123-7012 | |
| 15m | | 0.50µm | 240/250 | 123-7013 | |
| 30m | | 0.15µm | 250/260 | 123-7031 | |
| 30m | | 0.25µm | 250/260 | 123-7032 | |
| 30m | | 0.50µm | 240/250 | 123-7033 | |
| 60m | | 0.25µm | 250/260 | 123-7062 | |
| 60m | | 0.50µm | 240/250 | 123-7063 | |
| 0.45 | | 15m | 0.85µm | 230/240 | 124-7012* |
| | | 30m | 0.85µm | 230/240 | 124-7032* |
| | 0.53 | 15m | 0.50µm | 230/240 | 125-7017 |
| | | 15m | 1.00µm | 230/240 | 125-7012 |
| 30m | | 0.25µm | 230/240 | 125-7031 | |
| 30m | | 0.50µm | 230/240 | 125-7037 | |
| 30m | 1.00µm | 230/240 | 125-7032 | | |
| 60m | 1.00µm | 230/240 | 125-7062 | | |

*No special ferrules required for High Speed Megabore 0.45mm I.D.

DB-WAX-FF

- New! Columns are specially tested to separate 3 key fragrance components

This column-to-column reproducibility of the DB-WAX-FF brings high speed analysis of flavor/fragrance components on a polar column from the realm of the theoretically possible and makes it practical. While the DB-WAX-FF can be used for analysis suitable for microbore wax columns, it is designed and manufactured specifically for fragrance/flavors analysis. This column was originated from the Lavender oil quality analysis requirements.

| ID(mm) | Length | Film | Iso/Prog | Cat. No. |
|-------------|--------|--------|----------|-------------------|
| 0.10 | 20m | 0.20µm | 250/260 | 127-7023FF |

